


B G 7 9 0

INDUSTRIAL AC BARRIER GATE OPERATOR

Reliable gear-driven barrier operator for heavy-duty industrial applications.



SECURITY+ 2.0®

CONTINUOUS-DUTY 1/2 HP AC COMMERCIAL MOTOR

RELIABLE

HEAVY-DUTY COMMERCIAL MOTOR WITH 1/2 HP FOR STRONG, DEPENDABLE PERFORMANCE.

ACCESSIBLE LIMIT SETTINGS ADD CONVENIENCE TO UNIT INSTALLATION AND MAINTENANCE.

11-GAUGE STEEL ENCLOSURE FOR DURABILITY AND WEATHER RESISTANCE.

SMART

CONTROL INPUTS ALLOW CONNECTION OF OPTIONAL EXTERNAL DEVICES FOR SAFETY AND ACCESS CONTROL.

SAMS (SEQUENCED ACCESS MANAGEMENT SYSTEM) PROVIDES CONTROL BETWEEN BARRIER AND SLIDE/SWING GATE OPERATOR TO MAXIMIZE TRAFFIC FLOW.

SAFE AND SECURE

24-FT. WISHBONE ARM WITH RED AND WHITE STRIPES AND 2 COUNTERWEIGHTS INCLUDED.

SECURITY+ 2.0 SAFEGUARDS FACILITY ACCESS WITH ROLLING CODE TECHNOLOGY, OPENING FOR REGISTERED DEVICES ONLY.

RECOMMENDED ACCESSORIES:

SECURITY+ 2.0 COMMERCIAL ACCESS CONTROL RECEIVER

Standalone receiver provides high-capacity commercial access for a gate or commercial door operator.



STAR1000

SECURITY+ 2.0 LEARNING REMOTE CONTROL

Easily programmable to control up to 2 (892LT) or 4 (894LT) garage or gate operators; compatible with Security+® and can clone any LiftMaster® DIP technology.



892LT/894LT

ADDITIONAL OPTIONS:

PRIMARY/SECONDARY CONFIGURATION

Allows for reverse cabinet/rotation configuration.

90-3010

TIMER-TO-CLOSE

Optional module, programmable to 1–1,024 seconds for the unit to automatically close.



71-26438

HEATER

For use in extreme cold environments; 115V and 575V (G6518300), 208V and 460V (G6519084).



G6518300/G6519084

